



Regatron Power Supplies

DC Power Supplies TopCon Quadro Series
Overview Standard Types, valid from 15.04.09

Output voltage range (VDC)	Output power range (kW)	Output current range (A)	Dimensions (mm) width x height x depth	Weight (kg)	Type
0 – 52	0 – 20	0 – 500	19" x 9 U x 590	64	TC.P.20.52.480.S
0 – 52	0 – 32	0 – 700	19" x 9 U x 590	68	TC.P.32.52.480.S
0 – 65	0 – 20	0 – 385	19" x 9 U x 590	64	TC.P.20.65.480.S
0 – 65	0 – 32	0 – 600	19" x 9 U x 590	68	TC.P.32.65.480.S
0 – 100	0 – 20	0 – 250	19" x 9 U x 590	64	TC.P.20.100.480.S
0 – 100	0 – 32	0 – 400	19" x 9 U x 590	68	TC.P.32.100.480.S
0 – 130	0 – 20	0 – 192	19" x 9 U x 590	64	TC.P.20.130.480.S
0 – 130	0 – 32	0 – 308	19" x 9 U x 590	68	TC.P.32.130.480.S
0 – 200	0 – 20	0 – 125	19" x 9 U x 590	64	TC.P.20.200.480.S
0 – 200	0 – 32	0 – 200	19" x 9 U x 590	68	TC.P.32.200.480.S
0 – 400	0 – 20	0 – 63	19" x 9 U x 590	64	TC.P.20.400.480.S
0 – 400	0 – 32	0 – 100	19" x 9 U x 590	68	TC.P.32.400.480.S
0 – 500	0 – 20	0 – 50	19" x 9 U x 590	64	TC.P.20.500.480.S
0 – 500	0 – 32	0 – 80	19" x 9 U x 590	68	TC.P.32.500.480.S
0 – 600	0 – 20	0 – 40	19" x 9 U x 590	64	TC.P.20.600.480.S
0 – 600	0 – 32	0 – 66	19" x 9 U x 590	68	TC.P.32.600.480.S
0 – 800	0 – 20	0 – 32	19" x 9 U x 590	64	TC.P.20.800.480.S
0 – 800	0 – 32	0 – 50	19" x 9 U x 590	68	TC.P.32.800.480.S
0 – 1000	0 – 20	0 – 25	19" x 9 U x 590	64	TC.P.20.1000.480.S
0 – 1000	0 – 32	0 – 40	19" x 9 U x 590	68	TC.P.32.1000.480.S

- **AC line input: 3 x 432-528 VAC**, line frequency: 48-62 Hz
- Refer to type-specific technical datasheet for more detailed specifications.
- Contact factory for availability of models with output voltage ranges not listed here.

Regatron AG
Kirchstrasse 11
CH-9400 Rorschach
Switzerland

Tel +41 71 846 67 67
Fax +41 71 846 67 77
www.regatron.ch / mailbox@regatron.ch